	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
1	LAMINATED PARTITION				
	FULL HEIGHT PARTITION				
	Providing and fixing partition framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. The framing shall be finished with 12 mm thk. MDF board on both side and finished with 1.00 mm thk. texture/ ultra gloss matte Laminate in all direction/ combination and having 1.00 mm wide skirting in SS Satin brush metal laminate of make Archidlam/Green or approved equivalant including grooves as / Architect. Item include 65 x 65 mm teakwood member for door frame and additional framework and teakwood beading required for providing glazing. All exposed teakwood surface, grooves and the like to be finished in melamine polish of matching laminate colour including all necessary fitting and SS hardware of make dorma. The rate to include provision of extra frame work as necessary for skirting and making cut- outs for electrical switches, switch boxes, conduiting, door / glazing as per drawings. The edge beadings with steam beach wood should be finished with melamine.				
	8mm approved make clear float glass shall be provided above 2'-6" from ff.lvl. or as advised by architect/ bank with necessary steam beach moulding finished with melamine. The rate shall include necessary etching film / LOGO.	90.00	SQ.FT.		
2	LOW HEIGHT PARTITION				

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
	Providing and fixing partition framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm @ 600mm c/c both ways Horizontally and Vertically. The framing shall be finished with 12 mm thk. MDF board on both side and finished with 1.00 mm thk. texture/Ultra gloss matte Laminate finished with melamine polish. The shade of laminate and polishing finish to be got approved from Bank / Architect. The 1.00 mm wide skirtingin SS Satin brush metal laminate of make Archidlam/ Green or approved equivalant including grooves as / Architect. Rate shall be inclusive of necessary hardware items, etc. Complete. The rate to include for provision of extra frame work as necessary for skirting and making cut out for electrical switches, switch boxes, conducting, receiving A.C. etc. as per drawing.				
	A 70mm x 15mm steam beach moulding with champhered edge is to be provided on all external edges & finished in mellamine as per details. Providing and Fixing inserted Soft board / White boards / Glass maintaining the vertical surface lines and no extra measurements would be taken for the soft boards / Glass.	40.00	SQ.FT.		
3	WALL PANELLING OVER COLUMN & WALL Providing & Fixing of the wall panelling, made				
	of Heavy Duty Aluminium section 50x50mm @ 600 mm c/c both ways horizontally and vertically on				
	the wall providing over 12 mm thick MDF board with 1.00 mm thick Ultra / High Gloss laminated				
	of approved quality laminate and shade shall be				
	fixed on faces of panelling as per design with				
	groove, skirting shall be 100 mm high finished				
	with 1.00mm laminate. Wooden moulding ,lipping				
	etc.as directed by the bank.	1115.54	SQ.FT.		
4	CASH COUNTER PARTITION HT. UPTO 7'-0"				

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
	Providing & Fixing partition , made of Heavy Duty				
	Aluminium section 50x50mm @600mm c/c both				
	ways fixed rigidly at floor level as well as ceiling				
	bottom, 12 mm thick MDF board with 1.00mm				
	thick Ultra / High Gloss laminate of approved				
	quality and shade shall be fixed on both faces of				
	partition as per design with groove with				
	necessary openings for glass at 3'-10" height.				
	These openings shall be covered by 12mm thick				
	clear glass fixed with screw /clips covered with				
	TW beading on all four sides. Skirting shall be				
	100mm high with 1.00mm thick laminate.				
	The item includes door shutter of size 700mm				
	x200mm with frame work of 3 verticals and 5				
	horizontals made of 75mmx25mm .Heavy Duty				
	Aluminium sections and covered with 6mm thick				
	commercial plywood and Ultra / High Gloss				
	matte1.00mm laminate of approved quality and				
	shade with teak wood edging out of 40x20mm				
	teak wood section on all exposededges of shutter				
	(all around) with teak / rubber wood frame				
	(chowkhat) out of 75x50mm section Necessary openings for the glass shall be provided				
	in the top panel which shall be covered by				
	600mmx300mmx6mm thick glass with necessary				
	teak wood beadings. The item includes necessary				
	hardware such as hinges, tower				
	bolts,doorstopper,godrej night latch with 2 nos				
	SS (6" high) handle of approved quality and				
	decine				

BILL OF QUANTITIES FOR RENOVATION OF FURNISHING WORK AT CANARA BANK, PUNDRAK BRANCH, KARNAL. **GST EXTRA** S.No Particulars Quantity Unit Rate Amount All exposed teak /rubber wood surfaces shall be finished with approved colour melamine polish. The rate includes making provision for electrical 63.75 SQ.FT. conduits, switch and junction boxes. 5 CASH COUNTER Providing & fixing cash counter of length 1372 mm as per layout plan with writing top, upper top, front projection face, sides and front apron all shall be made of 19 mm thick comm. board (of bank approved) with teak wood lipping /moulding on exposed ends of comm. board. The front apron, projected face and exposed sides shall be finished with Ultra / High Gloss matte 1.00 mm thick laminate of approved shade and the upper top shall be provided with 20 mm thick pre-polished granite stone of approved shade (as per the sample/ Bank/ Architect approval). The writing top shall be finished with 1.50 mm thick laminate with TW moulding as per peer design .The skirting shall be 100 mm high finished with 1.00mm thick laminate.

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
	There shall be a CPU shelf of size 600mmx300mm				
	made of 19mm commercial board fixed at height				
	of 150 mm inside the counter with alround				
	teakwood lipping .There shall be wood foot rest				
	made of hollock wood .There shall be Metallic				
	key board tray (ebco make) . There shall be a				
	drawer unit consists of three drawer with all				
	round boxing made of 19 mm commercial board				
	with vertical support of the counter as one				
	side.The drawer shall be made of 19 mm				
	commercial block board . The drawer bottom and				
	rear side of the unit shall be covered by 6mm				
	commercial plywood. The front face ot the				
	drawer shall be covered by 1.00 mm thick				
	laminate of approved shade and make.Each				
	drawer shall have multipurpose lock (godrej),				
	drawer sliding channel and SS handle.All the				
	inner surfaces of drawer and table shall be				
	laminated finished .				
	The over all dimensions shall be:				
	Length = 1372 mm approx.				
	Width of writing top = 812 mm				
	Width of upper /customer top = 400 mm. height of writing platform = 750 mm				
	Height of customer platform above writing top=				
	cash cabin should be enclosed with AL. JALI on				
	top of cash cabin.	5.00	R.FT.		
5	GLASS FOR THE CASH CABIN (FRONT)				
	Providing and Fixing 12mm thick clear glass				
	supported by the side partitions and fixed				
	with brass clips on two sides/TW/rubber				
	·				
	wood beading .The exposed edges shall be				
	grinded and polished.	18.00	SQ.FT.		
7	GLASS FOR RUNNING COUNTER (FRONT)				
	Droviding and Fixing 12mm think along the				
	Providing and Fixing 12mm thick clear glass				
	9" - 1'-0" high for counter front supported by the				
	side partitions and fixed with brass clips on two				
	sides/TW/rubber wood beading .The exposed	g 00	SO ET		
	edges shall be grinded and polished.	8.00	SQ.FT.		

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
8	WORK STATION				
	Providing & fixing running counter as per layout				
	plan with writing top, sides and front apron all be				
	made of 19 mm thick comm. Board with teak				
	wood with lipping on exposed ends of comm.				
	board. The front apron shall be finished with				
	Ultra / High Gloss matte 1.00 mm thick laminate				
	of approved shade .The writing top shall be				
	provided with 1.5 mm thick laminate of approved				
	quality and shade (as per approved sample) with				
	TW / rubber wood mouling as per design . The				
	skirting shall be 100 mm high with 1.00 mm				
	laminate. 12 mm thick with counter top 2"x2" TW				
	member including polish (1'-0" high).				
	There shall be a CPU shelf of size 600mmx300mm				
	made of 19 mm comm. Block board fixed at				
	height of 150 mm inside the counter with alround				
	teakwood lipping. There shall be wood foot rest				
	made of hollock wood. There shall be Metallic Key				
	board trey(ebco make).				
	There shall be a drawer unit with each unit,				
	drawer unit consists of one drawer with storages				
	unit with alround boxing made of 19 mm comm.				
	Block board with vertical support of the counter				
	as one side. The overall dimension of the drawer				
	unit shall be 16" wide and 24" deep all made of				
	19 mm commercial block board . The drawer				
	bottom shall be made of 6 mm th.comm. ply and				
	rear side of the unit shall be covered by 19mm				
	th. commercial board .The front face of the				
	drawer shall be covered by 1mm lamination of				
	approved shade and make. Aii the inner surface of				
	drawer unit and table shall be laminated				
	finished. Each draw shall have multi purpose				
	lock (godrej) and SS handle.				
	The overall dimensions shall be: Length =1350 to				
	1500 mm , width of writing top = 750 mm height				
	of the writing platform = 750 mm.	12.00	R.FT.		

BILL OF QUANTITIES FOR RENOVATION OF FURNISHING WORK AT CANARA BANK, PUNDRAK BRANCH, KARNAL. **GST EXTRA** S.No Particulars Quantity Unit Rate Amount Providing and Fixing notice board /disply board, made of 50x25mm . Meerandi wood frame with 6mm thick comm.ply /particle board with 12mm thick board covered approved fabric, with 40x25 mm teak wood moulding all around 150.00 SQ.FT. finished with melamine polish. 10 CUP BOARD (Low Height) Providing & Fixing low ht. cabinet of height of cupboard shall be 750mm to 900mm with19mm th. Comm. Board , Ultra / High Gloss matte1.00mm thick laminate to be fixed all exposed surface (side, top, & front). The rate incldes necessary hardware such as hinges, godrej lock brass handle, beading to be polised, all the inner surface shall be laminated finised. 40.50 SQ.FT. FULLY GLAZED PARTITION - WITH TOUGHENED 11 GLASS **USING DORMA MAKE FITTINGS** Providing and fixing of Fixed Glass partition with 10mm thick toughened glass using PT Standard fittings like PT90/ PT92 of DORMA make at the top and grouting at the bottom with U - Shaped Aluminium rails and EPDM gaskets including cutting, making holes in glass and fixing the fittings in floors, false ceiling etc. and making the same good with necessary screw, sealent wherever required. The top PT standard fittings to be fitted to the Wooden section fixed above the Gypsum board in the level of GI channels of False ceiling. 40.00 SQ.FT. 12 GLASS DOOR WITH FLAMELESS ON PATCH

FITTING

	GST EXTRA				
.No	Particulars	Quantity	Unit	Rate	Amount
	Providing and fixing frameless fully glazed 12mm thk toughened float glass fixed with necessary patch fittings(Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, srews, sealent wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 12" long S. S. (C Shape) Handles of approved make, floor springs, and any necessary hardware items.(DORMA MAKE Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cilinder - US 10, Handle - TG 9300 EQ - S 25mm dia X 300mm length)				
		24.50	SQ.FT.		
3	FALSE CEILING (Armsstrong Grid)				
	P/F in position 600x 600x15 mm prima fine fissured tegular in 24 mm eposed tee white with trulok suspension systems with nrc value of 55 (acoustic performance) false ceiling of approved quality over M/S Armstrong world industries (india) Ltd trulok suspension systems of required weight as per architects app at reguired spacing, finishing of all joints neatly to proper line & level including providing of additional framework for electricals fixtures.including giving trap doors where ever required. Diffusers, cutouts for fire sprinklers etc. as per the specifications approved by architects Including necessary scaffolding supports, suspenders etc.	224.00	SQ.FT.		
4	FALSE CEILING (GYPSUM BOARD)				

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
	Providing & fixing false ceiling as per design consist of G.I.frame, which includes perimeter channels along with the parameter of ceiling, with intermediate channel of size 45 mmx0.9 mm thick with two flange of 15 mm each @ 1220 mm				
	c/c with ceiling angle of size 25x10x.5mm fixed to bottom of ceiling with G.I. cleat and steel expansion fastener, ceiling section of 0.55mm thick with knurled web of 51.5 mm and two flangesof 26 mm each with lips of 10.5 mm are then fixed to the intermediate channel with connecting clips and direction perpendicular to				
	the intermediate channel at 457mmc/c ,12.5mm thick Gypsum board shall be fixed with screw				
	paper tape and painted with two or more coats				
	of plastic emulsion paint over a cot of primer.				
	The item includes P/F perimeter channel of size				
	20x27x30mm and 0.55 mm thick for light fittings,				
	AC grills, diffusers and cutouts i/c cutting of				
	opening for light fixtures, A.C. etc. with 40x40mm				
	wooden moulding all around the walls / pillars.All				
	complete as per design .(The finished surface				
	area shall be measured.)	485.00	SQ.FT.		
15	TABLE (Laminated top)				
	Providing Table in position with writing top, sides and front apron all be made of 19mm thick comm. Board with teak wood lipping on exposed ends of comm. Board .The front apron and sides shall be finished with 1.00mm thick laminate of approved shade with Ultra / High Gloss matte. The writing top shall be provided with 1.00 mm thick laminate of approved shade(as per the sample). The exposed edges of the top shall be rounded on both the edges with teak/rubber wood moulding as per design .The skirting shall the shall be a CPU shelf of size 600 mm x 300mm made of 19 mm commercial block board fixed at height of 150 mm inside the counter with airound teakwood lipping.There shall be wood foot rest made of hollock wood.				
	There shall be key board tray made of 19 mm commercial block board with teak wood lipping				
1					

	GST EXTRA				
.No	Particulars	Quantity	Unit	Rate	Amount
	There shall be a drawer unit with alround boxing				
	made of 19 mm commercial block board with				
	vertical support of the counter as one sidde. All				
	made of 19 mm commercial block board. The drawer bottom and rear sidde of the unit shall be				
	covered by 6 mm commercial plywood. The front				
	face of the draw shall be covered by 1 mm				
	laminate of approved shade and make.Each draw				
	shallhave multipurpose lock (godrej) and SS				
	handle.				
	All the inner surrfaces of table , drawer unit and				
	shelves shall be laminated finished .				
	a) 1800 mm x900mm x 750 mm high, with drawer				
	unit consists of three drawer, mounted on sliding				
	channel (ebco make) (MANAGER TABLE)				
	6'-0" X 3'-0"	1	nos.		
6	SIDE STORAGE UNITS				
0	Providing & Fixing storage unit with sides, top,				
	bottom, shutter and shelves all be made of 19mm				
	thick comm. Board of approved quality and make				
	.The shelves shall be spaced at 450 mm c/c				
	.There shall be swing shutter.The rear side shall				
	be made of 6 mm thick comm. ply with laminate				
	finish. The top, sides, shutter and back finished				
	with Ultra / High Gloss matte 1.00 mm thick				
	laminate (in two shades) of approved quality and				
	shade as per design with groove .The exposed				
	edges of the board shall have teak wood lipping				
	.There shall be skirting 100 mm high made of 1				
	mm thick laminate. All the inner surface of				
	drawer and storage shall be laminated finished.				
	The rate includes necessary hardware such as				
	piano hinges, tower bolts, brass dead lock,				
	magnetic catchers, 4" long SS handle of approved				
	design.				
	a) The size of the storage unit shall be 3'-6" x2'-6'				
		3	nos.		
	x 1'-6" (deep) with 1.00 thick laminate on top.				
7	CENTRE/SIDE TARI E				
<u>′ </u>	CENTRE/SIDE TABLE				

	GST EXTRA				
S.No	Particulars	Quantity	Unit	Rate	Amount
	Providing in position table made of 50x50mm teak wood frame with 40x25 mm cross tie members on all four sides at top and bottom finised with melamine of approved colour and shade at top with 12 mm thick beveled edge tinted glass top. a) 600 mm x 600 mm x 400 mm	1	nos.		
	a) 000 mm x 000 mm x 400 mm				
18	Providing & Fixing 12 mm clear float glass on top of Manager tables . The exposed edges shall be grinded and polished.	20.00	SQ.FT.		
19	Poviding & Fixing door closer	3.00	Nos.		
20	Diluting and injecting chemical emulsion for POST - CONSTRUCTION anti - termite (including the cost of chemical emulsion) along the complete suface area of the wall, floor & ceiling using chemical emulsion @7.5 litres/sq.m. of the vetical surface of the substructure complete with chlopyriphos/ Lindane E.C.20% with 1% concentration.	500.00	SQ.FT.		
21	Providing & Fixing cheque dropping box of size 2'-6" x 2'-0" x 1'-0"" made of 12mm thick ply wood and finised with Ultra / High Gloss matte 1mm thick laminate with necessery opening, doors lock etc.	1	nos.		
22	Providing in position writing stand .The structure shall be made of 19 mm thick comm. Block board with 1.0mm thick laminate , shelf finished with Ultra / High Gloss matte 1 mm laminate with 12 mm thick beveled edge glass upper top in required shape, with 75 mm high 12 mm thick skirting exposed surface shall be stained to approved colour finised with melamine polish. The overall size shall be 4'-0"x1'-6"	1	nos.		
23	ROLLING SHUTTER BOXING				
	NOLEMO SHOTTEN DOMING				

BILL OF QUANTITIES FOR RENOVATION OF FURNISHING WORK AT CANARA BANK, PUNDRAK BRANCH, KARNAL. **GST EXTRA** S.No Particulars Quantity Unit Rate Amount Providing & Fixing ,framing consiting of 2 1/2" x 1 1/2" Al. frameing @ 600 mm c/c both ways horizontally and vertically on the rolling shutter ,providing over 6mm thick A.C.P. sheet, complete with necessary hardware, scaffolding 105.00 SQ.FT. etc.or as directed by the bank. 24 **VERTICAL BLINDS WITH SCOTCH GUARD** Providing & fixing in place 100 mm. Vertical blinds of approved make, quality and colour shade & pattern. Rate shall include necessary scotch guard treatment on both sides. The 80.00 SQ.FT. overlaps should be uniform & adequate. TOTAL **GST EXTRA**