

BOQ FOR FURNISHING ADDITIONS & ALTERATION WORKS AT CANARA BANK R.A.H SECTION, FIRST FLOOR, BNC, LUDHIANA.

S.No.	Item	Quantity	Units	Rate	Amount
PART-1 :INTERIOR WORKS					
1	DISMANTLING OF OLD CABIN PARTION				
	Remove of partly panelled and partly glazed wooden partitions/glazing/doors	1.00	l/s		
2	REPAIR OF GYPSUM BOARD CEILING				
	Repair of gypsum board ceiling after removal of existing damage ceiling and providing tapered edge Gypboard over a grid complete in all respects.	1.00	l/s		
3	PARTITION WITH GLASS (OVER EXISITNG PARTITIONS)				
	Providing & fixing partly glazed full height partition made of of 44 mm X 44 mm X 16 Gauge aluminium extruded sections @ 24" c/c vertically & horizontally. The bottom member shall be aluminium extruded sections of size 65 mm X 44 mm X 16 Gauge. The aluminium extruded sections frame shall be fixed rigidly at floor level with rawl plugs / steel lugs / screw. The frame work to be clad with 6mm thick ply and 1.0mm thick laminate as per pattern on both sides, with 6mm thick clear float glass fixed with teak wood beading as/ drawing, finished in melamine polish. All wood to be treated with wood preservatives of approved ISI quality, complete in all respect as/ instructions of Architect/ Engineer in charge.	135.00	sqft		
4	DOOR				
	Refixing existing wooden door from CM cabin complete in all respects.	1.00	l/s		
5	TABLES & COUNTERS				
	Providing and placing table made of 19mm thick commercial board and 1.0mm thick laminate. The front of the table top shall be projected as per drawing. Provision for 3" dia. Round / square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the counter. Teak wood lipping will be provided on all the edegs of the table and the drawers. The table shall have a laminated keyboard tray of size 600x450 fixed on channels, as per manufacturer's instructions / specifications. One drawer & cupboard below shall be provided on One Side of the Table. 0.8mm thick laminated surfaces i.e. inside leg space of table, inside drawers . Teak wood edegs / teak wood lipping / beading shall have melamine polished. The Table shall also include foot rest , as per drawing , complete in all respects.				
	Clerical Table: Size 4'-6"x2'-6"x2'-6"	6.00	no.		
6	LOW HEIGHT STORAGE CABINETS (2'-6" HIGH)				

S.No.	Item	Quantity	Units	Rate	Amount
	Providing & Fixing storage cabinets 2'-6" high & 18" deep as per drawings, having 2 sets of two filing drawers / Shutters as per drawings, made of 19 mm thick commercial board & 1.0mm thick laminate on all visible surfaces including open shelves. The drawers shall be made of 12mm thick (sides & back), 6mm thick plywood(bottom) & 19mm thick comm board (front fascia with laminate), with teak wood lipping on all edges, running on telescopic drawer channels . All the edges of beading / lipping shall be provided with melamine polish, complete in all respects.	17.00	rft.		
7	PAINT WORK				
	Interior(wall + ceiling)				
	Finishing wall with Interior paint of required shade two or more coats applied @ 3,28 liter per 10 sq meter over and including base coat of water proofing, complete in all respects.	500.00	sft		
	Total				